

■ ■ ■ ■ WARRANTY ■ ■ ■ ■

PLASTEEL® ELUTRON® Underground Petroleum/Motor Fuel Storage Tank

TANK OWNER NAME: _____

TANK OWNER ADDRESS: _____

TANK INSTALLATION ADDRESS: _____

TANK U.L. NUMBER: _____

TANK CAPACITY: _____

SHIPMENT DATE: _____

MANUFACTURER NAME: _____

MANUFACTURER ADDRESS: _____

MANUFACTURER TELEPHONE: _____

The manufacturer above is pleased to extend, on the U.L. numbered tank and installation above, when installed per our instructions, installed per N.F.P.A. Standard 30 for underground steel tanks, and upon receipt of completed and signed Certificate of Installation within 60 days of the installation completion date, the following warranty:

Provided that (i) Manufacturer shall have received a completed and signed Certificate of Installation from the tank owner in the form prescribed by Manufacturer, (ii) the tank in question shall have been installed in accordance with Manufacturer's installation instructions, and (iii) *the subject tank is maintained in accordance with **Steel Tank Institute** "Recommended Practice for Storage Tank Maintenance R111 Revision, 2nd Edition, March 2016", **Clean Diesel Fuel Alliance**, "Guidance for Underground Storage Tank Management at USLD Dispensing Facilities" and the **Coordinating Research Council (CRC) Report 672, July 2016, whichever is most applicable.***

The manufacturer above warrants the subject **PLASTEEL® ELUTRON® Underground Tank** when maintained per the recommended practices as listed as listed above:

- 1. to be free from defect in workmanship and materials for a period of five (5) years from the date of shipment;*
- 2. will not fail due to internal or external corrosion for a period of thirty (30) years from the date of shipment when used to store all motor fuels, including but not limited to, unleaded gasoline, leaded gasoline, gasohol in any alcohol blend percentages, 100% methanol, 100% ethanol, diesel fuel, jet fuel, kerosene, and fuel oil. Liquids are to be stored at atmospheric pressure and at a temperature not to exceed 150° (66°C). Consult manufacturer concerning other warranted liquids.*

The Warranty is specifically limited to the manufacturer's choice of one of the remedies set forth below in the event of a proven claim:

1. *Repair of the tank at our factory, freight charges not included.*
2. *Replacement of tank delivered to point of original delivery.*
3. *Refund of the original purchase price.*

This Warranty will be void unless written approval from the manufacturer, at our discretion, is effected before:

1. *Modification (s) is/are performed on the tank.*
2. *The tank is removed from the intended service.*
3. *The buried tank is removed to above grade.*

Owner must provide the manufacturer the opportunity to observe and inspect the tank prior to the removal of the buried tank to aboveground.

We are not liable for any labor, other installation or removal costs, indirect or consequential damages or any other damages in connection with these tanks.

Except as stated above, we make no warranty of merchantability, no warranty that our underground **PLASTEEL® ELUTRON®** tanks are fit for any particular purpose or use a do other warranty express or implied.